

ROUGH TERRAIN TRUCKS

4 WHEEL DRIVE 4000-5000KGS

ROYAL
FORK LIFTS



ENGINE

The PERKINS 1104C-44T engines' peak power 41.5kW and torque 413Nm at engine speeds as low as 1350rpm produces great responsiveness.

STEER AXLE

Oscillating steer axle allows either wheel to step over obstacles keeping the truck and load level.

LOW VIBRATION & NOISE

Divide-body chassis design with rubber mounting between the unitary overhead guard and chassis, plus full floating damping device of engine and turning bridge connected flexibly and full-curve acoustic absorption reduces the vibration and noise by 30%.

Rated Capacity	4000kg 5000kg
Load Centre	600mm 600mm
Lift Height	3000mm 3000mm
Free Lift Height	145mm 145mm
Mast Tilt Angle	15° 15°
Overhead Guard Height	2545mm 2545mm
Minimum Ground Clearance	320mm 320mm
Overall Length (with fork)	4837mm 4837mm
Minimum Turning Radius	3540mm 3540mm
Travel (laden)	21km/h 21km/h
Maximum Gradeability (laden)	30% 30%

*All Rights Reserved by RY Forklift.

Head Office: 01376 552135

Armill Lift Trucks Ltd
3a Crittall Drive
Springwood Industrial Estate
Braintree CM7 2RT

alt@armill.co.uk

ARMILL
LIFT TRUCKS