

# DIESEL FORK TRUCKS

1500-4500KGS

**ROYAL**  
FORK LIFTS



#### MAST TILT-CONTROLLED DEVICE (OPTION)

This allows Royal fork lifts to decelerate as the lifting height increases when the tilt angle is over 3 metres, preventing cargo from falling.

#### OPERATOR PRESENCE SECURITY SYSTEM (OPTION)

The fork lift can stop moving forward when the operator leaves the seat which helps avoid accidents and ensures the safety of goods and people.

#### PARKING BRAKE WARNING BUZZER (OPTION)

An automatic-style parking brake ensures convenience and safety. The warning buzzer will sound when the operator leaves the seat without parking the fork lift.

Rated Load Capacity	1500kg   1800kg   2000kg   2500kg   3000kg   3500kg   4000kg   4500kg
Load Centre	500mm
Rated Lift Height	3000mm
Free Lift Height	135mm - 140mm - 145mm - 150mm
Mast Tilt Angle	6°/10° - 6°/12°
Overhead Guard Height	2134mm - 2370mm
Ground Clearance (bottom of mast)	120mm - 170mm
Overall Width	1120mm - 1485mm
Turning Radius (outside)	2078mm - 2790mm
Travel Speed (full load)	13.5km/h - 19km/h
Maximum Gradeability (full load)	20.00%

\*All Rights Reserved by RY Forklift.

**Head Office: 01376 552135**

Armill Lift Trucks Ltd  
3a Crittall Drive  
Springwood Industrial Estate  
Braintree CM7 2RT

[alt@armill.co.uk](mailto:alt@armill.co.uk)

**ARMILL**  
LIFT TRUCKS